



FOCUSED ON APPLICATION HVAC

Handling Unit operates for Heating and Cooling



\* Garantía 1 ( uno ) Año en partes

Air Handler Unit ( Information)		
AHU Model:	CAHU-E-210L	
Capacity Nominal:	17.50 Tons	
Capacity Total:	62.70 Kw	17.84 Tons
Capacity Sensible:	45.30 Kw	12.89 Tons
Width:	1,430.00 mm	56.30 in
Length:	1,406.00 mm	55.35 in
Height:	1,102.00 mm	43.39 in
Shipping Weight:	342.00 Kgs	753.98 Lbs
Voltaje Nominal:	230-460V/3Ph/60Hz	

Air Flow		
Supply Air Flow:	10,000.00 m <sup>3</sup> /Hr	5,885.77 Cfm
Supply Air Fan Ext Pressure:	270.00 Pa	1.084 In CA
Supply Air ESP:	160.00 Pa	0.642 In CA

Unit Specification		
Install Locate:	Indoor	
Door Direction:	Left Type	
Inner / Bottom Panel:	0.50 mm GI	0.02 in GI
Inner / Top Panel:	0.50 mm GI	0.02 in GI
Panel Thick:	25.00 mm	0.98 in
Base Frame Height:	80.00 mm	3.15 in
Outer Panel:	0.45mm Pre-coated Steel	
Insulation Material:	Polyurethane	
Base Frame Material:	Steel Plate	
Unit Install Type:	Floor Mounted	

Open Filter		
Filter Depth:	10.00 mm	0.39 in
Face Velocity:	2.15 m/s	423.23 ft/min
Filter Type:	G2	
Media Material:	Nylon	
Size / Qty:	681mm X 475 mm	4.00 Pieces
Air Pressure Drop:	10.00 Pa	0.040 In CA
Ext. Direction	Side Extraction	
Brand:	Starndard	
Install Mode:	Sliding Type	
Frame Material:	Galvanize Steel	

Cooling Coil		
Supply Air Flow:	10,000.00 m <sup>3</sup> /Hr	5,885.77 Cfm
Face Velocity:	2.73 m/s	537.40 ft/min
Coil Model:	3PWP4D-34Tx1180(DN40)	
Fin Material:	Hyprophilic Al	
Frame Material:	Galvanized Seel	
Tube Direct:	Left Type	

Cooling Coil		
Number of Coils:	1.00 Pieces	
Tupe Material:	Cooper Pipe	
Heater Material:	Seamless Steel Pipe	
Heater Diameter:	DM 40 Ø	1.50 In Ø
Mousture Eliminator:	None	
DP Material:	Standard	

Water Side Condition Heating		
Capacity Total:	129.20 Kw	36.77 Tons
Entering Water Temp:	60.00 °C	140.00 °F
Leaving Water Temp:	48.80 °C	119.84 °F
Water Flow:	2.75 L/s	43.59 Gpm
Water Pressure Drop (WPD):	54.40 kPa	18.1997 ft CA

Water Side Condition Cooling		
Capacity Total:	62.70 Kw	17.84 Tons
Capacity Sensible:	45.30 Kw	12.89 Tons
Entering Water Temp:	7.00 °C	44.60 °F
Leaving Water Temp:	12.30 °C	54.14 °F
Water Flow:	2.84 L/s	45.01 Gpm
Water Pressure Drop (WPD):	57.40 kPa	19.2033 ft CA

Air Side Condition Heating		
Entering Air Temp (DB ):	15.00 °C	59.00 °F
Entering Air Temp (WB):	12.00 °C	53.60 °F
Leaving Air Temp (DB ):	53.30 °C	127.94 °F
Leaving Air Temp (WB):	13.20 °C	55.76 °F
Air Pressure Drop:	100.00 Pa	0.401 In CA

Air Side Condition Cooling		
Entering Air Temp (DB ):	27.00 °C	80.60 °F
Entering Air Temp (WB):	19.50 °C	67.10 °F
Leaving Air Temp (DB ):	13.50 °C	56.30 °F
Leaving Air Temp (WB):	13.10 °C	55.58 °F
Air Pressure Drop:	100.00 Pa	0.401 In CA



### SUPPLY AIR FAN

Acces Door:	Standard	
Supply Air Flow:	10,000.00 m <sup>3</sup> /Hr	5,885.77 Cfm
Fan Brand:	Langdi	
Fan Bearing:	Standard	
Fan Model:	LDT18-13LK	
Supply Air Fan:	FT	
Blade Type:	Forward Curved	
Fan Speed:	658.20 Rpm	
Fan Speed Limit:	1,200.00 Rpm	
Fan Shaft Power:	1.80 Kw	
Fan Outlet Air Velocity:	13.50 m/s	2,657.48 ft/min
Fan Total Efficiency:	59.90%	
Fan Static Efficiency:	42.60%	
Fan Pulley:	SPZ250-2-2012	
Fan Pulley Bush:	2012/35	
Air Outlet Type:	Flange	

### SUPPLY AIR FAN

Acces Direction:	Left type	
TPS:	270.00 Pa	1.084 In CA
Motor Brand:	Brook	
Motor Type (reinforced):	Inverter Duty motor W/O FCF	
Motor Type:	NOT INCLUDE frequency inverter	
Motor Velocity:	1 (ONE) Constant Speed	
Motor (Power-Pole):	3.00 Kw - 4P	4.02 Hp - 4P
Motor Energy Efficiency:	IE3	230-460V/3Ph/60Hz
Motor location:	SM	
Wiring Direct:	Left type	
Motor Pulley:	SPZ95-2-1610	
Motor Pulley Bush:	1610/28	
Air Outlet Size:	478mm X 430mm	18.82in X 16.93in
Belt:	SPZ1362	
Air Outlet Location:	Front Panel	

**INVERTER DUTY MOTOR:** Indica que el Motor esta reforzado para poder operar con variador de frecuencia pero sin el variador el motor opera a velocidad constante.

### SOUND POWER

Sound Power:	63.00 Hz	125.00 Hz	250.00 Hz	500.00 Hz	1.00 kHz	2.00 kHz	4.00 kHz	8.00 kHz	Total dB(A)
Inlet Lwl (A):	56.1	66.1	71.1	74.1	75.1	72.1	70.1	64.1	80.1
Outlet LwO (A):	59.1	69.1	74.1	77.1	78.1	75.1	73.1	67.1	83.2
Type Lw (A):	55.7	59.2	64.6	63.4	64.9	62.4	55.1	24.9	70.6

### UNIT DIMENSIONS

